

# EN39 Standard galvanised scaffold tubes 48.3mm Diameter 3.2mm 245N/mm2 Yield Strength

## **Basic Information**

Place of Origin: China

Brand Name: Bythai Scaffolding

Certification: SGS ISO
 Model Number: BT201
 Minimum Order 1000

Quantity:

Price: \$10-\$85
Packaging Details: In bundles
Delivery Time: 10-15 days
Payment Terms: TT/TC

• Supply Ability: 1000tons per month



# **Product Specification**

Material: Galvanised Steel

Yield Strength: 245N/mm2
Diameter: 48.3mm
Application: Scaffolding
Standard: EN39
Weight: 6.4kg/m

Name: Galvanised Scaffold Tube

• Thickness: 3.2mm

• Highlight: 48.3mm Scaffold Tubes, 3.2mm Scaffold Tubes,

245N/mm2 Scaffold Tubes



# More Images



### **Product Description**

## **Product Description:**

The tube is coated with a galvanized finish, which provides excellent corrosion resistance and ensures that the tube is long-lasting and reliable. The galvanized finish also makes the tube easy to clean and maintain, ensuring that it remains in top condition for years to come. This product is designed for use in tube and coupler scaffolding systems, which are commonly used in construction and building projects. The tube is made to the EN39 standard, ensuring that it meets the highest quality and safety standards.

Whether you are building a new structure or performing maintenance on an existing one, the Galvanised Scaffold Tube is an excellent choice for your scaffolding needs. It is easy to install and can be used in a variety of applications, including tube scaffolding systems.

#### **Features:**

Product Name: Galvanised Scaffold Tube

Thickness: 3.2mm Yield Strength: 245N/mm2 Material: Galvanised Steel Diameter: 48.3mm Weight: 6.4kg/m

Galvanised scaffold tubes are made of hot dip galvanized scaffolding steel tube, which is known for its durability and resistance to rust and corrosion. These tubes are commonly used in construction and building projects, providing a strong and reliable support structure. Additionally, scaffold aluminum tube is also available for those who prefer a lightweight and easy-to-handle option.

#### **Technical Parameters:**

Name:	Galvanised Scaffold Tube
Material:	Galvanised Steel
Diameter:	48.3mm
Thickness:	3.2mm
Weight:	6.4kg/m
Tensile Strength:	420N/mm2
Yield Strength:	245N/mm2
Standard:	EN39
Surface Treatment:	Galvanised
Application:	Scaffolding

#### **Applications:**

The galvanised scaffold tube is made of high-quality galvanised steel and has a weight of 6.4kg/m. The yield strength of the tube is 245N/mm2, making it strong enough to withstand heavy loads and rigorous use. The diameter of the tube is 48.3mm, which is a standard size for scaffolding applications.

The galvanised scaffold tube is commonly used in construction sites for supporting heavy loads and providing a stable platform for workers to perform their tasks. It is also used in various industrial applications, including mining, oil and gas, and shipbuilding. The galvanised coating on the tube provides protection against corrosion, making it suitable for use in harsh environments.

The Bythai Scaffolding galvanised scaffold tube is easy to assemble and disassemble, making it a convenient option for temporary structures. The tubes can be connected using various scaffolding clamps, making it adaptable to different shapes and sizes. The product is also compliant with EN39 standards, ensuring its quality and safety.

The galvanised scaffold tube is available in bundles and can be shipped to your location within the specified delivery time. Whether you need it for a construction project or an industrial application, the Bythai Scaffolding galvanised scaffold tube is a reliable and durable option that will meet your needs.







No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China